


A-350L



- New style incorporates throat opening equal to or larger than old style hooks.
- Each product has a Product Identification Code (PIC) for material traceability, along with a Working Load Limit, and the name Crosby or “CG” forged into it.
- All hooks incorporate Crosby’s patented QUIC-CHECK® deformation indicators to help in determining if throat opening dimension has changed.
- Each hook is equipped with a Crosby S-4320 heavy duty stamped latch with the high cycle, long life spring.
- Forged alloy steel, Quenched & Tempered.



4

A-350L Sliding Choker Hook




Single Part Rope Size (in)	Eight Part Rope Size (in)	Stock No.	WLL (lb)	Weight Each (lb)	Dimensions (in)												Hook Frame Code	Replacement Latch Kit Stock No.
					A	B	C	D	E	F	G	H	L	P	R	AA*		
3/8	-	1011802	2500	1.0	2.06	1.13	.63	2.41	.63	.38	.84	.91	4.28	2.59	.63	1.50	DA	1096325
1/2	1/8	1011811	3800	1.4	2.25	1.31	.75	2.97	.78	.50	.97	1.06	4.97	3.09	.75	1.50	FA	1096374
† 5/8	-	1011820	5800	3.0	3.06	1.63	.75	3.56	.94	.56	1.13	1.31	6.38	3.88	1.00	2.00	GA	1096421
† 5/8	3/16	1011839	5800	2.7	3.06	1.63	1.00	3.56	.94	.56	1.13	1.31	6.38	4.00	1.13	2.00	GA	1096421
† 3/4	-	1011848	8200	4.4	3.38	2.13	1.00	4.25	1.16	.63	1.44	1.63	7.66	4.58	1.13	2.50	HA	1096468
† 3/4	1/4	1011857	8200	3.8	3.38	2.13	1.44	4.25	1.16	.63	1.44	1.63	7.66	4.78	1.13	2.50	HA	1096468
†† 7/8-1	-	1028177	15000	9.70	4.41	2.12	1.25	6.06	1.41	.88	2.00	2.33	9.55	5.72	1.50	3.00	IA	1096515

*Deformation indicators. †Determine eye diameter “C” before ordering. ††7/8-1” is cast steel.

G-3315



- Forged carbon steel, Quenched & Tempered.
- Pressed steel latches and stainless steel springs, bolts and nuts.
- For replacement latch kit, order Stock No. 9900299.
- Hook body - galvanized.
- Do not attach slings or other devices in hook for overhead lifting.



G-3315 Snap Hook



Hook Size (in)	Stock No.	Working Load Limit (lb)*	Weight Each (lb)	Dimensions (in)							
				A	B	C	D	E	F	L	R
7/16	1023056	750	.23	.25	.75	.75	.44	2.25	.75	3.94	3.25
9/16	1023074	1000	.48	.34	1.12	.81	.56	2.69	.88	4.75	3.84

4:1 Design Factor.