

GRADE 100, CAM-ALLOY CHAIN

Chain

- Specifically Recommended for Overhead Lifting Applications
- 25% Stronger Than Grade 80 Which Enables You to Perform. Same Lifts with Lighter Weight Chain
- Standard Material: Alloy Steel, Heat Treated
- Standard Finish: Bright
- Hallmarking: "C10", "USA" and Traceability Code
- Proof Tested
- Design Factor: 4 to 1
- Packaged in Drums, Order Unit is "Feet"
- Made in the USA
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Catalog No.	UPC No. 020418	Material Diameter	Inside Length	Inside Width	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
5/16 in	0400512	063367	0.32 in	0.94 in	0.46 in	4500 lb	500 ft	12.8	460 lb
1 in	0401612	063510	1.00 in	2.80 in	1.40 in	47700 lb	100 ft	4.3	965 lb
1 - 1/4 in	0402012	063534	1.25 in	3.50 in	1.75 in	72300 lb	60 ft	3.5	915 lb

GRADE 100, CAM-ALLOY CHAIN

- Specifically Recommended for Overhead Lifting Applications
- Standard Material: Alloy Steel, Heat Treated
- Standard Finish: Bright
- Hallmarking: "C8", "USA" and Traceability Code
- Proof Tested
- Design Factor: 4 to 1
- Packaged in Drums, Order Unit is "Feet"
- Made in the USA
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Catalog No.	UPC No. 020418	Material Diameter	Inside Length	Inside Width	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
9/32 in	0405212	182204	0.29 in	0.87 in	0.41 in	4300 lb	500 ft	13.8	370 lb
5/16 in	0405312	245510	0.33 in	1.01 in	0.50 in	5700 lb	500 ft	12	520 lb
3/8 in	0405412	182211	0.40 in	1.22 in	0.57 in	8800 lb	500 ft	10	740 lb
1/2 in	0405512	182228	0.52 in	1.58 in	0.75 in	15000 lb	300 ft	7.8	750 lb
5/8 in	0405612	182235	0.64 in	1.93 in	0.87 in	22600 lb	200 ft	6.5	758 lb
3/4 in	0405712	182242	0.80 in	2.42 in	1.09 in	35300 lb	100 ft	5.5	598 lb
7/8 in	0405812	152924	0.88 in	2.70 in	1.28 in	42700 lb	100 ft	4.4	775 lb



the
carpenter
group



GRADE 70, TRANSPORT CHAIN - DRUMS

Chain

- Designed for Use in Load Binding, Towing, Logging and Other Applications Requiring High Strength
- Can Be Used in Accordance with Department of Transportation Regulations
- Standard Material: Heat Treated Carbon Steel
- Standard Finish: Zinc Electroplate with Yellow Chromate Conversion Coating
- Hallmarking: "C7" and "USA"
- Proof Tested
- Design Factor: 4 to 1
- Packaged in Drums, Order Unit is "Feet"
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Catalog No.	UPC No.	Material Diameter	Inside Length	Inside Width	Finish	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
1/4 in	0510412	063763	0.31 in	0.94 in	0.46 in	Yellow Chromate	3150 lb	800 ft	12.8	752 lb
5/16 in	0510512	063800	0.33 in	1.15 in	0.48 in	Yellow Chromate	4700 lb	550 ft	10.4	561 lb
3/8 in	0510612	063848	0.40 in	1.36 in	0.57 in	Yellow Chromate	6600 lb	400 ft	8.8	600 lb
7/16 in	0510712	063886	0.47 in	1.29 in	0.67 in	Yellow Chromate	8750 lb	300 ft	9.3	636 lb
1/2 in	0510812	063916	0.53 in	1.70 in	0.75 in	Yellow Chromate	11300 lb	200 ft	7.1	520 lb

GRADE 70, TRANSPORT CHAIN - ROUND PAILS

- Designed for Use in Load Binding, Towing, Logging and Other Applications Requiring High Strength
- Can Be Used in Accordance with Department of Transportation Regulations
- Standard Material: Heat Treated Carbon Steel
- Standard Finish: Zinc Electroplate with Yellow Chromate Conversion Coating
- Hallmarking: "C7" and "USA"
- Proof Tested
- Design Factor: 4 to 1
- Packaged in Pails, Order Unit is "Each"
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Catalog No.	UPC No.	Material Diameter	Inside Length	Inside Width	Finish	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
1/4 in	0510413	063770	0.31 in	0.94 in	0.46 in	Yellow Chromate	3150 lb	150 ft	12.8	139 lb
5/16 in	0510513	063817	0.33 in	1.15 in	0.48 in	Yellow Chromate	4700 lb	100 ft	10.4	102 lb
3/8 in	0510613	063855	0.40 in	1.36 in	0.57 in	Yellow Chromate	6600 lb	75 ft	8.8	113 lb



the
carpenter
group



GRADE 70, TRANSPORT CHAIN - SQUARE PAILS

Chain

- Designed for Use in Load Binding, Towing, Logging and Other Applications Requiring High Strength
- Can Be Used in Accordance with Department of Transportation Regulations
- Standard Material: Heat Treated Carbon Steel
- Standard Finish: Zinc Electroplate with Yellow Chromate Conversion Coating
- Hallmarking: "C7" and "USA"
- Proof Tested
- Design Factor: 4 to 1
- Packaged in Pails, Order Unit is "Each"
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Catalog No.	UPC No. 020418	Material Diameter	Inside Length	Inside Width	Finish	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
1/4 in	0510426	183867	0.31 in	0.94 in	0.46 in	Yellow Chromate	3150 lb	65 ft	12.8	64 lb
5/16 in	0510526	183874	0.33 in	1.15 in	0.48 in	Yellow Chromate	4700 lb	50 ft	10.4	51 lb
3/8 in	0510626	186639	0.40 in	1.36 in	0.57 in	Yellow Chromate	6600 lb	45 ft	8.8	68 lb

GRADE 30, PROOF COIL CHAIN - DRUMS

- Excellent Low Carbon Steel Chain for General Purpose Applications
- Frequently Used for Fabricating Tow Chains, Binding and Logging Chains, Marine and Other General Applications
- Standard Finish: Self Colored, Zinc Plated or Galvanized
- Hallmarking: "C3" and "USA" on 5/16" and Larger
- Proof Tested
- Design Factor: 4 to 1
- Packaged in Drums, Order Unit is "Feet"
- Made in the USA
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Self-Colored		Zinc-Plated		Galvanized		Material Diameter	Inside Length	Inside Width	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
	Catalog No.	UPC No. 020418	Catalog No.	UPC No. 020418	Catalog No.	UPC No. 020418							
1/8 in	0120202	056932	-	-	0120232	056949	0.16 in	0.89 in	0.29 in	400 lb	1000 ft	13.5	190 lb
3/16 in	0120302	056970	0120322	057007	0120332	057045	0.21 in	0.95 in	0.34 in	800 lb	1000 ft	12.6	350 lb
1/4 in	0120402	057076	0120422	057106	0120432	057144	0.26 in	1.20 in	0.45 in	1300 lb	800 ft	10	460 lb
5/16 in	0120502	057205	0120522	057243	0120532	057281	0.31 in	1.27 in	0.47 in	1900 lb	550 ft	9.4	482 lb
3/8 in	0120602	057335	0120622	057373	0120632	057410	0.37 in	1.36 in	0.57 in	2650 lb	400 ft	8.8	500 lb
7/16 in	-	-	-	-	0120732	057489	0.47 in	1.37 in	0.75 in	3700 lb	300 ft	8.8	660 lb
1/2 in	0120802	057502	0120822	057526	0120832	057557	0.48 in	1.70 in	0.75 in	4500 lb	200 ft	7.1	420 lb
5/8 in	0121002	057595	-	-	0121032	057618	0.66 in	2.10 in	0.87 in	6900 lb	150 ft	5.7	610 lb
3/4 in	0121202	057632	-	-	0121232	057656	0.78 in	2.70 in	1.02 in	10600 lb	100 ft	4.4	560 lb



the
carpenter
group



GRADE 30, PROOF COIL CHAIN - ROUND PAILS

Chain

- Excellent Low Carbon Steel Chain for General Purpose Applications
- Frequently Used for Fabricating Tow Chains, Binding and Logging Chains, Marine and Other General Applications
- Standard Finish: Zinc Plated or Galvanized
- Hallmarking: "C3" and "USA" on 5/16" and Larger
- Proof Tested
- Design Factor: 4 to 1
- Packaged in Pails, Order Unit is "Each"
- Made in the USA
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Zinc Plated		Galvanized		Material Diameter	Inside Length	Inside Width	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
	Catalog No.	020418	Catalog No.	020418							
3/16 in	0140323	057991	0140333	058004	0.21 in	0.95 in	0.34 in	800 lb	250 ft	12.6	88 lb
1/4 in	0140423	058028	0140433	058035	0.26 in	1.20 in	0.45 in	1300 lb	141 ft	10	79 lb
5/16 in	0140523	058059	0140533	058066	0.31 in	1.27 in	0.47 in	1900 lb	92 ft	9.4	76 lb
3/8 in	0140623	058080	0140633	058097	0.37 in	1.36 in	0.57 in	2650 lb	63 ft	8.8	79 lb
1/2 in	0140823	058103	-	-	0.48 in	1.70 in	0.75 in	4500 lb	40 ft	7.1	95 lb

GRADE 30, ANCHOR LEAD, PROOF COIL CHAIN - SQUARE PAILS

- Excellent Low Carbon Steel Chain for General Purpose Applications
- Frequently Used As Anchor Lead Chain for Marine Applications
- Standard Finish: Galvanized and Polycoated White
- Hallmarking: "C3" and "USA" on 5/16" and Larger
- Proof Tested
- Design Factor: 4 to 1
- Order Unit is "Each"
- Made in the USA
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Catalog No.	UPC No. 020418	Material Diameter	Inside Length	Inside Width	Finish	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
5/16 in	0200356	183881	0.31 in	1.27 in	0.47 in	Galvanized & Polycoated White	1900 lb	75 ft	9.4	62 lb



the
carpenter
group



GRADE 30, PROOF COIL CHAIN - SQUARE PAILS

Chain

- Excellent Low Carbon Steel Chain for General Purpose Applications
- Frequently Used for Fabricating Tow Chains, Binding and Logging Chains, Marine and Other General Applications
- Standard Finish: Zinc Plated or Galvanized
- Hallmarking: "C3" and "USA" on 5/16" and Larger
- Proof Tested
- Design Factor: 4 to 1
- Packaged in Pails, Order Unit is "Each"
- Made in the USA
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Self-Colored		Zinc Plated		Galvanized		Material Diameter	Inside Length	Inside Width	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
	Catalog No.	UPC No. 020418	Catalog No.	UPC No. 020418	Catalog No.	UPC No. 020418							
1/8 in	-	-	0143226	190360	-	-	0.16 in	0.89 in	0.29 in	400 lb	200 ft	13.5	38 lb
3/16 in	-	-	0143326	183058	0143336	183065	0.21 in	0.95 in	0.34 in	800 lb	150 ft	12.6	53 lb
1/4 in	-	-	0143426	183072	0143436	183089	0.26 in	1.20 in	0.45 in	1300 lb	100 ft	10	56 lb
5/16 in	0143516	190681	0143526	183096	0143536	183102	0.31 in	1.27 in	0.47 in	1900 lb	75 ft	9.4	62 lb
3/8 in	-	-	0143626	183119	0143636	183126	0.37 in	1.36 in	0.57 in	2650 lb	45 ft	8.8	56 lb

GRADE 30, POLYCOATED, PROOF COIL CHAIN - SQUARE PAILS

- Excellent Low Carbon Steel Chain for General Purpose Applications
- Frequently Used for Swing Sets, Borders, Crowd Control and Other General Applications
- Standard Finish: Polycoated Yellow or Hi-Visibility Orange
- Hallmarking: "C3" and "USA" on 5/16" and Larger
- Proof Tested
- Design Factor: 4 to 1
- Order Unit is "Each"
- Made in the USA
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Catalog No.	UPC No. 020418	Material Diameter	Inside Length	Inside Width	Finish	Working Load Limit	Feet Per Package	Links Per Foot	Per Package	Shelf Pack
1/4 in	PD0143426	212185	0.26 in	1.20 in	0.45 in	Yellow Polycoat	1300 lb	75 ft	10	45 lb	1
5/16 in	HV0142526	187940	0.31 in	1.27 in	0.47 in	Hi-Visibility Orange Polycoat	1900 lb	75 ft	9.4	62 lb	1



the
carpenter
group



GRADE 30, PROOF COIL CHAIN - REELS

Chain

- Excellent Low Carbon Steel Chain for General Purpose Applications
- Frequently Used for Swing Sets, Borders, Crowd Control and Other General Applications
- Standard Finish: Zinc Plated or Polycoated Yellow
- Hallmarking: "C3" and "USA" on 5/16" and Larger
- Proof Tested
- Design Factor: 4 to 1
- Packaged on Reels, Order Unit is "Each"
- Made in the USA
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Zinc Plated		Yellow Polycoat		Material Diameter	Inside Length	Inside Width	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
	Catalog No.	UPC No. 020418	Catalog No.	UPC No. 020418							
3/16 in	0725027	064982	PD0725027	184642	0.21 in	0.95 in	0.34 in	800 lb	100 ft	10.75	38 lb
1/4 in	0722127	183270	-	-	0.26 in	1.20 in	0.45 in	1300 lb	65 ft	10.75	41 lb
1/4 in	-	-	PD0722127	183393	0.26 in	1.20 in	0.45 in	1300 lb	60 ft	10.75	36 lb
5/16 in	0722227	183287	-	-	0.31 in	1.27 in	0.47 in	1900 lb	60 ft	10.75	50 lb
3/8 in	0722327	183294	-	-	0.37 in	1.36 in	0.57 in	2650 lb	35 ft	10.75	44 lb

MOORING CHAIN - DRUMS

- Excellent Low Carbon Steel Chain with A Long Link Design for Mooring Applications
- The Longer Link Allows the Use of A Shackle Anywhere in the Length of Chain, Not Just at End Links
- Greater Working Load Limit Than Proof Coil
- Hot Dipped Galvanized Finish
- Hallmarking: "MC" and "USA"
- Proof Tested
- Design Factor: 4 to 1
- Made in the USA
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Catalog No.	UPC No. 020418	Material Diameter	Inside Length	Inside Width	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
3/8 in	0129332	152108	0.41 in	1.23 in	0.62 in	3700 lb	400 ft	9.7	536 lb
1/2 in	0129432	152092	0.51 in	2.05 in	0.83 in	6000 lb	200 ft	8	460 lb
5/8 in	0129532	152078	0.63 in	2.52 in	0.94 in	9000 lb	150 ft	4.7	510 lb
3/4 in	0129632	152085	0.79 in	3.00 in	1.16 in	13500 lb	100 ft	4	554 lb



the
carpenter
group



GRADE 43, HIGH TEST CHAIN - DRUMS

Chain

- Designed for Use in Load Binding, Towing, Logging and Other Applications Requiring High Strength
- Standard Material: Carbon Steel
- Standard Finish: Self Colored or Bright, Zinc Plated or Galvanized
- Hallmarking: "C4" All Sizes and "USA" on 1/4" and 5/16"
- Proof Tested
- Design Factor: 3 to 1
- Packaged in Drums, Order Unit is "Feet"
- Made in the USA
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Catalog No.	UPC No. 020418	Material Diameter	Inside Length	Inside Width	Finish	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
1/4 in	0180412	058769	0.28 in	1.20 in	0.45 in	Self-Colored	2600 lb	800 ft	10	504 lb
1/4 in	0180422	058790	0.28 in	1.20 in	0.45 in	Zinc Plated	2600 lb	800 ft	10	504 lb
1/4 in	0180432	058820	0.28 in	1.20 in	0.45 in	Galvanized	2600 lb	800 ft	10	504 lb
5/16 in	0180512	058851	0.33 in	1.27 in	0.47 in	Self-Colored	3900 lb	550 ft	9.4	523 lb
5/16 in	0180522	058882	0.33 in	1.27 in	0.47 in	Zinc Plated	3900 lb	550 ft	9.4	523 lb
5/16 in	0180532	058912	0.33 in	1.27 in	0.47 in	Galvanized	3900 lb	550 ft	9.4	523 lb
3/8 in	0180612	058943	0.38 in	1.36 in	0.58 in	Self-Colored	5400 lb	400 ft	8.8	520 lb
3/8 in	0180632	059018	0.38 in	1.36 in	0.58 in	Galvanized	5400 lb	400 ft	8.8	520 lb
1/2 in	0180812	059094	0.53 in	1.70 in	0.75 in	Self-Colored	9200 lb	200 ft	7.1	520 lb
1/2 in	0180832	059155	0.53 in	1.70 in	0.75 in	Galvanized	9200 lb	200 ft	7.1	520 lb
5/8 in	0181012	059186	0.66 in	1.94 in	0.93 in	Bright	13000 lb	150 ft	6.2	534 lb
5/8 in	0181032	059216	0.66 in	1.94 in	0.93 in	Galvanized	13000 lb	150 ft	6.2	534 lb
3/4 in	0181212	059254	0.78 in	2.21 in	1.10 in	Bright	20200 lb	100 ft	5.4	581 lb

GRADE 43, POLYCOATED, HIGH TEST CHAIN - SQUARE PAILS

- Designed for Use in Load Binding, Towing, Logging and Other Applications Requiring High Strength
- Standard Material: Carbon Steel
- Standard Finish: Polycoated Hi-Visibility Orange
- Hallmarking: "C4" All Sizes and "USA" on 1/4" and 5/16"
- Proof Tested
- Design Factor: 3 to 1
- Packaged in Pails, Order Unit is "Each"
- Made in the USA
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Catalog No.	UPC No. 020418	Material Diameter	Inside Length	Inside Width	Finish	Working Load Limit	Feet Per Package	Links Per Foot	Per Package
5/16 in	HV0184526	187698	0.33 in	1.27 in	0.47 in	Hi-Visibility Orange Polycoat	3900 lb	60 ft	9.4	50 lb



the
carpenter
group



GRADE 43, HIGH TEST CHAIN - ROUND PAILS

Chain

- Designed for Use in Load Binding, Towing, Logging and Other Applications Requiring High Strength
- Standard Material: Carbon Steel
- Standard Finish: Bright and Zinc Plated
- Hallmarking: "C4" All Sizes and "USA" on 1/4" and 5/16"
- Proof Tested
- Design Factor: 3 to 1
- Packaged in Pails, Order Unit is "Each"
- Made in the USA
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Bright		Zinc Plated		Material Diameter	Inside Length	Inside Width	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
	No.	020418	No.	020418							
1/4 in	0181413	059278	0181423	059285	0.28 in	1.20 in	0.45 in	2600 lb	150 ft	10	98 lb
5/16 in	0181513	059292	0181523	059308	0.33 in	1.27 in	0.47 in	3900 lb	100 ft	9.4	95 lb
3/8 in	0181613	059315	0181623	059322	0.38 in	1.36 in	0.58 in	5400 lb	75 ft	8.8	98 lb

GRADE 43, HIGH TEST CHAIN - SQUARE PAILS

- Designed for Use in Load Binding, Towing, Logging and Other Applications Requiring High Strength
- Standard Material: Carbon Steel
- Standard Finish: Bright and Galvanized
- Hallmarking: "C4" All Sizes and "USA" on 1/4" and 5/16"
- Proof Tested
- Design Factor: 3 to 1
- Packaged in Pails, Order Unit is "Each"
- Made in the USA
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Bright		Galvanized		Material Diameter	Inside Length	Inside Width	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
	Catalog No.	UPC No. 020418	Catalog No.	UPC No. 020418+							
1/4 in	0184416	183133	-	-	0.28 in	1.20 in	0.45 in	2600 lb	100 ft	10	66 lb
5/16 in	0184516	183140	0184536	185878	0.33 in	1.27 in	0.47 in	3900 lb	60 ft	9.4	57 lb
3/8 in	0184616	183157	0184636	185885	0.38 in	1.36 in	0.58 in	5400 lb	40 ft	8.8	52 lb



the
carpenter
group



- Uses: Food Processing, Chemical and Marine Applications, Wherever Non-Magnetic, Electrically Welded Corrosion Resistant Chain is Needed
- Standard Material: Type 316L Stainless
- Standard Finish: Bright
- Hallmarking: "316"
- Proof Tested
- Design Factor: 4 to 1
- Cut to Order, Order Unit is "Feet"
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT
- Working load limits (WLL) shown are room temperatures. Reduce WLL by 15% for temperatures up to 250°F, 25% between 250°F and 800°F, 33% between 800°F and 1000°F, 50% between 1000°F and 1200°F, and 60% between 1200°F and 1400°F.



Trade Size	Catalog No.	UPC No. 020418	Material Diameter	Inside Length	Inside Width	Working Load Limit	Links Per Foot	Weight Per 100 Feet (lbs)
5/32 in	0192411	177422	0.156 in	0.89 in	0.28 in	500 lb	15.6	21
3/16 in	0192711	176043	0.196 in	0.91 in	0.34 in	930 lb	13.2	41
1/4 in	0192911	176050	0.250 in	1.00 in	0.43 in	1570 lb	12	75
5/16 in	0193111	176067	0.312 in	1.03 in	0.49 in	2400 lb	11.7	95
3/8 in	0193311	176074	0.394 in	1.22 in	0.51 in	3550 lb	9.8	138

STAINLESS STEEL QUICK LINKS

- For Fast and Easy Connections Between Two Lengths of Chain
- Do Not Use to Support Human Weight, for Playground or Athletic Equipment, or as a Safety Device




Figure No.	Trade Size	Catalog No.	UPC No. 020418	Finish	Mat. Dia. (A)	Length (B)	Opening (C)	Inside Length (D)	Inside Width (E)	Packaged	Working Load Limit	Weight Each	Shelf Pack	Case Pack
7350	1/8 in	T7630506	193460	Polished	0.137 in	1.45 in	0.19 in	1.18 in	0.41 in	Bulk, UPCTag	220 lb	0.02 lb	10	100
7350	3/16 in	T7630526	193477	Polished	0.195 in	1.94 in	0.24 in	1.56 in	0.53 in	Bulk, UPCTag	660 lb	0.04 lb	10	100
7350	1/4 in	T7630536	193484	Polished	0.230 in	2.28 in	0.30 in	1.83 in	0.60 in	Bulk, UPCTag	880 lb	0.08 lb	10	100
7350	5/16 in	T7630546	193491	Polished	0.310 in	2.93 in	0.38 in	2.34 in	0.73 in	Bulk, UPCTag	1540 lb	0.18 lb	10	100
7350	3/8 in	T7630556	193507	Polished	0.350 in	3.24 in	0.39 in	2.56 in	0.78 in	Bulk, UPCTag	1540 lb	0.24 lb	10	100