



Stop sleeve are available in either aluminum or copper in a wide variety of sizes ranging from 1/32" to 3/8" inclusive. When properly applied with Locoloc® Hand Swager to bare cable on 3x7, 7x7, 7x19 and 6x19 constructions stop sleeves capable of holding only 1/3 to 1/2 of the rated breaking strength of the cable to which they are attached. All sizes and types are bulk packaged. Plain copper supplied unless otherwise specified.

MADE IN THE USA: YES

To fit Cable Dia.	Aluminum Stop Sleeves		Copper Stop Sleeves
	Part No.		ST2-1
1/32	Use Tool No.	Available in Copper Only	000-WCI or #5-H
	Wgt. Lbs. M/Pcs.		0.8
	Part No.		ST2-1.5
3/64	Use Tool No.	Available in Copper Only	000-WCI, 0-1.5-3FS, 0-3/64SC or #5-H
	Wgt. Lbs. M/Pcs.		1.5
	Part No.	ST1-2	ST2-2
1/16	Use Tool No.	0-1/16SC, 000-WCI, #5-H, or SL7NDK-R	
	Wgt. Lbs. M/Pcs.	0.4	2
	Part No.	ST1-3	ST2-3
3/32	Use Tool No.	0-1.5-3-FS, 0-3/32SC, #1-SC, #1-BSC, #1-P, #5-H, SL-7ND346-R, or SL-7NDK-R	
	Wgt. Lbs. M/Pcs.	2.5	8
	Part No.	ST1-4	ST2-4
1/8	Use Tool No.	0-1.5-3FS, 0-3/32SC, #1-SC, #1-BSC, #1-P, #5H, SL-7ND346-R, or SL-7NDK-R	
	Wgt. Lbs. M/Pcs.	2.3	7
	Part No.	ST1-5	ST2-5
5/32	Use Tool No.	0-1/8SC, #1-SC, #1-BSC, #1-P, #5-H, or SL-7NDK-R	
	Wgt. Lbs. M/Pcs.	4	12
	Part No.	ST1-6	ST2-6
3/16	Use Tool No.	0-1/8SC, #1-SC, #1-BSC, #1-P, #5-H, SL-7ND346-R, or SL-7NDK-R	
	Wgt. Lbs. M/Pcs.	3.5	10.5
	Part No.	ST1-7	ST2-7
7/32	Use Tool No.	0-1/8SC, #1-SC, #1-BSC, #1-P, #5-H, or SL-7NDK-R	
	Wgt. Lbs. M/Pcs.	6.7	18.6
	Part No.	ST1-8	ST2-8
1/4	Use Tool No.	0-1/4, #3-H, #5-H, or SL-7NDK-R	
	Wgt. Lbs. M/Pcs.	21	61
	Part No.		ST2-10
5/16	Use Tool No.	Available in Copper Only	0-1/4, #3-H, #5-H, or SL-7NDK-R
	Wgt. Lbs. M/Pcs.		52
	Part No.		ST2-12
3/8	Use Tool No.	Available in Copper Only	0-1/4, #3-H, #5-H, or SL-7NDK-R
	Wgt. Lbs. M/Pcs.		44

